




Diaphragm Pumps for Air, Gases and Vapours



Similar to original product

Series LABOPOINT® Pump N 840.1.2 FT.18

LABOPOINT® Chemically-resistant Diaphragm Vacuum Pump

Technical features:

- 100% oil-free transfer
- Pure transferring and evacuation of gases
- Highly compatible with vapors and condensate
- Chemically-resistant
- Therefore suitable for highly aggressive or corrosive gases and vapors
- Maintenance-free
- Environmentally friendly
- Gastight, leakage rate approx. 6×10^{-3} mbar x l/s, not tested in serial production
- ATEX-compliant according to ATEX II 2G IIB+H2 T3X internal atmosphere only

The chemically-resistant diaphragm pump series N 840.1.2 is a double-head, dry-running device used in a wide range of laboratory applications. These pump transfer and pump down without contamination.

The heart of this very compact pump is a KNF structured diaphragm. This patented diaphragm was stress-optimized using the Finite Elements method. As a result, we were able to make the pump smaller while increasing the service life of the diaphragm.

Technical data: N 840.1.2 FT.18

Delivery (l/min) ¹⁾	60
Ultimate vacuum (mbar abs.)	90
Operating pressure (bar g)	1
Connectors for tube (mm)	ID 10
Permissible gas and ambient temperature	+5...+40 °C
Mains	230V/50Hz
Motor protection	IP 44
Power P ₁	270 W
Operating current	1.9 A
Weight	12.6 kg
Dimensions L x H x W (mm)	341/226/160
With thermal switch and power fuse	

Motors with other voltages and frequencies on request.

¹⁾ at atm. pressure

Material in contact with the pumped media

Type/Order No.	Pump head	Diaphragm	Valves
N 840.1.2 FT.18	TFM™ PTFE	PTFE-coated	FFPM

Spare parts


Description	Order No.
Spares kit	057359




Diaphragm Pumps for Air, Gases and Vapours

Dimensions and performance characteristics

Pump down time for 10 l receiver



Performance characteristics



Dimensions (mm)

